

Liqui-Sol™ Your Option for Safety, Storage & Disposal!




Sprayon® Liqui-Sol™ is your option for safety, storage and disposal. Preserve, Prevent and Protect your equipment safely with Sprayon's new and improved Liqui-Sol MRO chemical program. Liqui-Sol eliminates expensive disposal costs, is 100% recyclable and is safe for work and plant environments.



PRESERVE. PROTECT. PREVENT.™

SAFETY FIRST, PERFORMANCE FOLLOWS

FEATURES	BENEFITS
Green House Gas Free 	Partner with Sprayon in the removal of Green House gases from your facilities
Available in 22 proven MRO formulas	Covers most MRO maintenance needs
100% Disposable	Eliminates expensive disposal costs
Durable Aluminum Spill Proof Package	Reuse or Recycle
Safe for Workers & Plant Environments	Free your-self of safety concerns regarding storage, application, and disposal
NSF Certified	Acceptable for use in food processing facilities

LUBRICANTS



LU™100 White Lithium Grease is a high solids white grease that provides excellent lubrication for metal-to-metal applications. It is ideal for use on chains, gears, drives, and hinges.

- High-solids, non-staining white grease
- Will not drip or run on vertical surfaces
- Effective from -20°F to +275°F



LU™103 Rust Breaker™ is a fast-acting product that quickly loosens rust while penetrating grease and dirt. A transparent, non-staining oil, its light film displaces moisture and acts as a corrosion preventative.

- Loosens and frees seized fasteners
- Quickly loosens rust while penetrating grease and dirt
- Superior water displacing, creep, and penetrating properties



LU™201L Open Gear & Wire Rope Lubricant is an extreme pressure performance lube that penetrates the pores of metal surfaces to reach the core of wire rope. This heavy duty lubricant provides a wide range of lubrication at high temperatures while adhering extremely well to surfaces.

- Withstands extreme pressure with maximum adhesion
- Works from 0°F to 450°F
- Won't wash, weather away or rub off



LU™202L Moly Chain Lubricant is a high viscosity oil that clings to moving parts. Foaming action penetrates close tolerances of chain drive bushings and pins to provide long-lasting lubrication. Reduces friction wear on moving parts and in metal-to-metal applications.

- Reduces wear, increases chain life
- Moly additive assures lubrication under extreme pressure
- Effective from -20°F to +300°F



LU™206L All-Purpose Silicone Lubricant protects against air and moisture to retard oxidation and corrosion. It virtually eliminates friction and sticking to improve high-speed production. Leaves a long lasting film that is compatible with most surfaces.

- Compatible with most surfaces; will not attack most plastics
- Will not interfere with painting or decorating
- Effective from -50°F to +375°F



LU™208L Cutting Oil is an excellent lubricant specifically formulated for all ferrous and non-ferrous machining operations. Extends tool life, reducing tool sharpening and downtime.

- Extends tool life
- Recommended for all metals
- Clings to surface



LU™210L Food Grade Silicone Lubricant is a colorless, odorless, low-viscosity silicone lubricant that is compatible with most surfaces. Ideal for use in close proximity to foods where petroleum products and other organics would contaminate.

- Meets FDA regulations when no more than 1 ppm is applied
- Will not attack delicate surfaces such as styrene or urethane
- Effective from -58°F to 450°F



LU™700L Food Grade Machinery Oil penetrates and loosens dirt, scale, and corrosion. Provides effective lubrication to free up rusted or corroded parts.

- Non-silicone formula
- Virtually odorless, tasteless and colorless
- Meets FDA regulation 12.878, 178.3620, and 573.680



LU™711L The Protector™ All-Purpose Lubricant is a general maintenance penetrant unmatched in its versatility and quality. Known as The Protector™, it's the clear-cut choice of industry to penetrate, lubricate, demineralize and inhibit corrosion.

- Protects metal surfaces from corrosive elements
- Eliminates short circuits in electrical applications
- Formulated to ensure maximum moisture displacement



LU™777L Outdoor Metal Protectant is a waxy corrosion preventative that offers excellent lubrication and long-term outdoor protection. Its tacky film provides an excellent barrier to salt spray and high humidity.

- A waxy, heavy-duty, rust inhibitor
- Offers 24-month durability to stand up to the most severe weather conditions
- MIL-C-16173D Grade 2, MIL-C-23411A



LU™204L Dry Film Graphite Lubricant is a high lubricity graphite that adheres to most surfaces with minimum surface preparation. It air dries rapidly at room temperature to provide clean, long-wearing lubrication.

- Dries Rapidly
- Reduces Friction And Wear
- Effective up to 850F constant and 1000F intermittent



LU™708L High Performance Dry Lubricant is a clean, non-oily, non-staining, versatile dry lubricant that functions from -40F to + 572F. It is clean, chemically inert formula that dries quickly to a white film to show coverage. This product does not contain silicone or chlorinated solvents.

- Safe On Most Plastics
- Lowest Coefficient Of Friction
- Dries quickly to a white, chemically inert film

NEW

ELECTRICAL & ELECTRONIC



EL™2302L Electrical Contact Cleaner is a non-ozone depleting cleaner that removes oil, grease and dirt from sensitive equipment and precision instruments leaving no residue. It is non-conductive and safe on most plastics.

- No CFCs or HCFCs
- Leaves no residue
- Meets California's Consumer Regulation (CONS-1) for Electrical Cleaner

EL™749L Electrical Degreaser is a heavy-duty cleaner that penetrates fast to remove dirt, oil, grease, wax and tar. Leaves no residue. Contains no Class I or Class II compounds.

- For use on Non-Energized equipment
- Leaves no residue
- Fast-evaporating
- Meets California's Consumer Regulation (CONS-1) for Electrical Cleaner



EL™2846L Non-Chlorinated Electrical Degreaser is a non-flammable, fast-evaporating cleaner/degreaser that penetrates instantly to remove dirt, oil, grease and wax. Increases the life of electrical components by removing foreign materials that can cause costly downtime.

- No Hazardous Air Pollutants
- Safe on all ferrous and non-ferrous metals; most plastics
- Non-chlorinated, Non-flammable, Non-ozone-depleting

EL™848L Flash Free® Electrical Degreaser is a non-flammable, fast-evaporating cleaner that penetrates instantly to remove dirt, oil, grease and wax. It's versatility allows for many MRO Cleaning operations found in industrial plants.

- Penetrates easily, evaporates quickly, leaves no residue
- Chlorinated, Non-flammable, non-ozone-depleting
- Meets California's Consumer Regulation (CONS-1) for Energized Electrical Cleaner



EL™2204L Electronic Contact Cleaner cleans sensitive equipment and precision instruments quickly without temperature control problems. Instant evaporation eliminates trapping of airborne contaminants and allows parts to be handled immediately. Because it is non-conductive, equipment can be cleaned while operating.

- Leaves No Residue
- Non-Conductive, Non-Flammable
- Safe On Metal And Many Plastics



NEW

CLEANER & DEGREASERS

CD™757L Heavy-Duty Citrus Degreaser is a multi-purpose degreaser and graffiti remover. This non-chlorinated formula has the cleaning power of solvents to remove grime, dirt, grease, and oil.

- Biodegradable, heavy-duty, multi-purpose cleaner and graffiti remover
- Pleasant citrus scent
- No chlorinated solvents

CD™880L General Purpose Cleaner is an excellent cleaner for hard surfaces that are not ordinarily damaged by water. This streak proof formula cuts through dirt, grease, soil surface smears and finger marks.

- All-purpose formula that cuts through dirt with ease
- Safe to use on metal, finished wood, porcelain, vinyl, leather, laminated surfaces and glass
- Cleans spots on synthetic carpets

CD™885L Stainless Steel Cleaner polishes, brightens, cleans and protects stainless steel and other metal surfaces, such as chrome and aluminum. Polishes to a non-greasy film. Invisible coating resists further soiling, fingerprints, water marks and rusting.

- Water-based emulsion formula
- Resists corrosion
- Cleans and shines



SPECIALTY

SP™607L Belt Dressing conditions belts while increasing pulling power up to 50% even when subjected to wet or out-door conditions. Will not glaze, collect dirt or dust. Reduces squeaky noise caused by old "V" belts.

- Can be applied directly to belts while running
- Contains no asphalt or rosin
- Will not glaze or collect dirt or dust

SP™705L Non-chlorinated Brake & Parts Cleaner instantly flushes away brake fluids, grease and dirt to ensure accurate adjustments and smooth brake operations. This non-chlorinated formula is also recommended as a cleaner for metal parts.

- Non-Chlorinated
- Fast Evaporating
- Leaves No Residue



NEW

LUBRICANTS – PRODUCT CHARACTERISTICS

Item #	Stock #	Description	Liqui-Sol™ Bulk Refill (5 Gal)	Flash Point (°F)	Dielectric Strength (ODP)	Ozone Depletion Potential	Chlorinated Solvents	Fill Level	NSF Rating	NSF Registration	Plastics Safe	Low Temp	High Range	Load Capacity¹	Penetrant	Water Displacer	Rust Inhibitor	Paintable	% Actives	Viscosity²
LU™100	A000100LQ	White Lithium Grease	S10005000	75°F	n/a	No	No	14 fl oz	H2	127752	Yes	(-20°F)	275°F	M	Yes	Yes	Yes	n/a	n/a	n/a
LU™103	A000103LQ	Rust Breaker Penetrant	S10305000	>200°F	47,400	No	No	14 fl oz	H2	127753	Yes	20°F	450°F	L	Yes	Yes	Yes	n/a	n/a	n/a
LU™201L	A000201LQ	Open Gear & Wire Rope Lubricant	S20105000	50°F	n/a	No	No	14 fl oz	n/a	n/a	n/a	0°F	450°F	EP	Yes	Yes	Yes	n/a	n/a	n/a
LU™202L	A000202LQ	Moly Chain Lubricant	S20205000	50°F	n/a	No	No	14 fl oz	H2	127755	Yes	(-20°F)	300°F	EP	Yes	Yes	Yes	n/a	n/a	n/a
LU™206L	A000206LQ	All-Purpose Silicone Lubricant	S20605000	85°F	n/a	No	No	14 fl oz	n/a	n/a	Yes	(-50°F)	375°F	L	Yes	Yes	Yes	Yes	5	M
LU™208L	A000208LQ	Cutting Oil	S20805000	n/a	10,000	No	No	14 fl oz	H2	127756	Yes	20°F	500°F	L	Yes	Yes	Yes	n/a	n/a	n/a
LU™210L	A000210LQ	Food Grade Silicone Lubricant	S21005000	75°F	n/a	No	No	14 fl oz	H1	127743	Yes	(-58°F)	450°F	L	Yes	n/a	Yes	No	5	L
LU™700L	A000700LQ	Food Grade Machinery Oil	S70005000	>200°F	n/a	No	No	14 fl oz	H1	127744	Yes	20°F	355°F	L	Yes	No	Yes	No	n/a	n/a
LU™711L	A000711LQ	The Protector™ All-Purpose Lubricant	S71105000	140°F	47,000	No	No	14 fl oz	H2	115051	Yes	20°F	500°F	L	Yes	Yes	Yes	n/a	n/a	n/a
LU™777L	A000777LQ	Outdoor Metal Protectant	S77705000	121°F	30,000	No	No	14 fl oz	H2	127748	Yes	20°F	300°F	M	Yes	Yes	Yes	n/a	n/a	n/a
LU™204L	A000204LQ	Dry Film Graphite Lubricant	S20405000	15°F	n/a	No	No	14 fl oz	n/a	n/a	n/a	-40°F	850°F	M	Yes	Yes	Yes	No	n/a	n/a
LU™708L	A000708LQ	High Performance Dry Lubricant	S70805000	15°F	n/a	No	No	14 fl oz	n/a	n/a	n/a	-40°F	572°F	M	Yes	Yes	Yes	No	n/a	n/a

* Test on non-essential piece before using 1. Load Capacity: L=Low M=Medium EP=Extreme Pressure 2. Viscosity Range: L=Low M=Medium H=High

CLEANER & DEGREASERS – PRODUCT CHARACTERISTICS

Item #	Stock #	Description	Liqui-Sol™ Bulk Refill (5 Gal)	Flash Point (°F)	Dielectric Strength (Volts)	Ozone Depletion Potential (ODP)	Chlorinated Solvents	Fill Level	NSF Rating	NSF Registration	Plastics Safe	KB Solvency¹	Residue	Evaporation Rate
CD™757L	A020757LQ	Heavy-Duty Citrus Degreaser	S75705000	100°F	40,400	No	No	14 fl oz	C1	127513	No	56	n/a	n/a
CD™880L	A020880LQ	General Purpose Cleaner	S88005000	<215°F	n/a	No	No	14 fl oz	C1	127751	Yes*	n/a	n/a	n/a
CD™885L	A020885LQ	Stainless Steel Cleaner	S88505000	None	n/a	No	No	14 fl oz	C1	127742	Yes*	n/a	n/a	n/a

* Test on non-essential piece before using 1. The higher the number, the stronger the cleaner

ELECTRICAL & ELECTRONIC – PRODUCT CHARACTERISTICS

Item #	Stock #	Description	Liqui-Sol™ Bulk Refill (5 Gal)	Flash Point (°F)	Dielectric Strength (Volts)	Ozone Depletion Potential (ODP)	Chlorinated Solvents	Fill Level	NSF Rating	NSF Registration	Plastics Safe	KB Solvency¹	Residue	Evaporation Rate
EL™2302L	A002302LQ	Electrical Contact Cleaner	S23020500	40°F	n/a	No	No	14 fl oz	K2	127547	Yes*	342	No	Fast
EL™749L	A020749LQ	Electrical Degreaser	S74905000	85°F	n/a	No	No	14 fl oz	K2	127514	No	85	No	Very Fast
EL™2846L	A020847LQ	Non-Chlorinated Electrical Degreaser	S20846050	None	15,000	No	No	14 fl oz	K2	127546	Yes*	129	No	Very Fast
EL™848L	A020846LQ	Flash Free® Electrical Degreaser	S84805000	None	37,000	No	Yes	14 fl oz	K2	127741	Yes	129	No	Fast
EL™2204L	A002204LQ	Electronic Contact Cleaner	n/a	None	26,800	Class II	Yes	14 fl oz	n/a	n/a	Yes	31	No	Very Fast

* Test on non-essential piece before using 1. The higher the number, the stronger the cleaner

SPECIALTY – PRODUCT CHARACTERISTICS

Item #	Stock #	Description	Liqui-Sol™ Bulk Refill (5 Gal)	Flash Point (°F)	Dielectric Strength (Volts)	Ozone Depletion Potential (ODP)	Chlorinated Solvents	Fill Level	NSF Rating	NSF Registration	Plastics Safe	KB Solvency¹	Residue	Evaporation Rate
SP™607L	A000607LQ	Belt Dressing	S60705000	53°F	n/a	No	No	14 fl oz	P1	127750	Yes	n/a	n/a	n/a
SP™705L	A000705LQ	Non-Chlorinated Brake & Parts Cleaner	S70505000	17°F	n/a	no	no	14 fl oz	n/a	n/a	No	n/a	No	Very Fast

* Test on non-essential piece before using 1. The higher the number, the stronger the cleaner

SPRAYON® LIQUI-SOL™ SECONDARY CONTAINER PROGRAM

Item #	Description
66190B120	Liqui-Sol Aluminum Threaded Can
86311151	Liqui-Sol Mixer 1.6 cc Trigger Sprayer
A000099LQ	Liqui-Sol Refill Kit (12 cans, 12 closures, 12 triggers)

©2011 Sprayon® Products Made in U.S.A.



Distributed by:

PRESERVE. PROTECT. PREVENT.™



Sprayon® Products
 101 Prospect Ave. NW
 Cleveland, OH 44115
www.Sprayon.com
 1-800-777-2966

310-B015-000